

## Fuse - SI FORM C 30 A DIN 72581 - 0913760

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Flat-type plug-in fuse, type C, color code: light green, nominal current: 30 A

The figure shows a version of the article

### Product Features

- With snap-in foot for secure pre-assembly on the PCB
- Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V

### Key commercial data

Packing unit	1 1
GTIN	 4 017918 104009
Weight per Piece (excluding packing)	1.55 GRM
Custom tariff number	85361050
Country of origin	Germany

### Technical data

#### General

Color	light green
Inflammability class according to UL 94	V0
Fuse	C
Nominal current $I_N$	30 A
Nominal voltage $U_N$	24 V

#### Dimensions

Width	5 mm
Length	19 mm
Height NS 35/7,5	13 mm

# Fuse - SI FORM C 30 A DIN 72581 - 0913760

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 6.0	27142001
eCl@ss 7.0	27142008
eCl@ss 8.0	27142008

### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298

### UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121412

## Approvals

### Approvals

---

Approvals

GOST

---


Ex Approvals

---

Approvals submitted

---

### Approval details

GOST 
------------------------------------------------------------------------------------------

