



NOTES:

- 1) BASE: UL94V0, GLASS FILLED PA66, BLACK  
M5 STUDS: ZINC-PLATED STEEL  
COVER: THERMOPLASTIC ELASTOMER, BLACK  
HEX NUTS: STEEL  
LOCK WASHERS: STEEL
- 2) MAX FUSE RATING: 200A
- 3) M5 STUD TORQUE: 3-5.0 Nm MAX  
MOUNTING TORQUE: WITH M4 BOLTS AND WASHERS: 5Nm MAX
- 4) TEMPERATURE RATING: -40°C TO 125°C

**METRIC**  
ASSEMBLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.  
DIMENSIONS IN BRACKETS [ ] ARE INCHES  
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

©	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS. -MINIMUM CPK VALUE
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP	DENOTES CP DIMENSIONS. -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

4	SPLIT LOCK WASHER, M5	EA	2
3	HEX NUT, M5X.8	EA	2
2	COVER	EA	1
1	BASE	EA	1
NO COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL		MATERIAL SPEC	
SEE NOTES		SEE NOTES	
FINISH		SCALE 1:1	
DATE	10/18/12	DATE	10/18/12
DRW	PVN	CHK	SUPER DR
DATE		DATE	
APPD		DATE	
8	17	53	
TOLERANCES UNLESS OTHERWISE SPECIFIED (REF. ISO 2768-MK)			
DIMENSION	0.5 - 1.3	1.3 - 3.0	3.0 - 120
TOLERANCE	±0.1	±0.2	±0.3
3RD ANGLE PROJECTION			
TITLE FLEX-MIDI FUSE HOLDER			
REVISION DRWG. NO. OL-04981038HXFC			
LITTELFUSE CHICAGO, USA 773-628-1000			
COPIES TO		GRAMS/PIECE	
1	9	18	
2	10	19	
3	12	20	
4	13	21	
5	14	23	
6	15	33	
7	16	43	
8	17	53	
LTR	DATE	REVISION	CHK
B	10/18/12	RELEASE FOR PRODUCTION. PCA 50000006363, 10/18/12	PN