muRata Inductor Data S	Sheet				
LQW15AN7N3J8	*#" indicates a package	specification code.			
In Production General 125 (Mound (Non))	te High Per Q Reflow OK RoHS REA	сн			
< List of part numbers with package codes > LQW15AN7N3J80D ,LQW15AN7N3J80B					
Shape		Note	es		
	n	necessary Please ap operating Please co	ng temperature exceeding +85°C, y for LQW15A_80 series. oply the derating curve shown in cl temperature. onfirm "Notice (Rating)". erences Specifications \$4180mm Paper taping	-	
L size	1.0 ±0.1mm	В	Packing in bulk	500	
W size	0.6 ±0.1mm				
T size	0.5 ±0.1 mm		Mass (Typ.)		
Size code in inch (mm)	0402 (1005)	1 piece 0.0009g			

Specifications

Inductance	7.3nH ±5%
Inductance test frequency	100MHz
Rated current (Itemp) (Based on Temperature rise)	1700mA
Max. of DC resistance	0.050Ω
Q (min.)	32
Q test frequency	250MHz
Self resonance frequency (min.)	7.0GHz
Operating temperature range (Self-temperature rise is not included)	-55∼125°C
Series	LQW15AN_80

🔔 Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


1 of 2



Q-Frequency characteristics (Typ.)







2 of 2

🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.