



LEAD FINISH: SOLDER	
BUSHING FINISH: SILVER	
CAPACITANCE	5500pF
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C 100 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
50	50
100	--
200	70
1-10 GHz	70
SCHEMATIC	
MARKING:	
PART: M15733/61-0008	
BAG: MIL 15733/61-0008	
OLSP2	
DATE CODE	
100VDC, 70VAC/400Hz	
125°C	
10 AMPS	
XXX QTY/BAG (100 MAX.)	
P.O. XXX	
PACKAGE: TO BE MARKED SAME AS THE BAG.	

CN 57806-ENG	43	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL INC.	Dwn. KAUFFMAN	Description Pi		
	42		Fractions ± 1/64					
	CN 184970		Dec. .xx±				Date 2-23-11	RESIN SEAL FILTER
	REDRAWN		Dec. .xxx±.010				Apvd.	
	CHANGE NOTICE		Angles ±0° 30'				Scale NONE	
			CODE IDENT. NO. OLSP2		51-712-063			